



## NITROCELLULOSE PAINTS

N.C Paints are based on nitrocellulose resin with combination of plasticizing resins. These have very good adhesion on metals, Plastics and leathers.

### SPECIFICATION OF N.C. PAINTS

<b>Finish on H.G</b>	7
<b>Viscosity</b>	Thick
<b>Dilution Viscosity</b>	30-35 See with 2:1 Dilution
<b>S.G</b>	1.00 -1.10 Varies as per Shade
<b>Drying</b>	S-D Less than 10 Minutes H-D Less than 1 Hour
<b>Method of application</b>	Spraying
<b>Thinner recommended</b>	Chemilac AC N.C Thinner
<b>Application Viscosity</b>	18-20 Sec
<b>Shelf Life</b>	6 Months

#### NOTE

All information gives in this sheet are accurate to the best of our knowledge, no warranty given and no liability is accepted in respect of such information as conditions of applications are beyond our control.

#### PACK SIZE

20 Liters , 4 Liters

#### CONTACT :

**The Chemicals of India**

(Prop. Chemilac Paints Pvt. Ltd.)

Plot No 36, Sector 27C, Faridabad-121003. Haryana

**Phone** : 91-129-2277382, 2277392

**Fax** : 91-129-2271607

**Email** : info@chemilac.com

visit us at : [www.chemilac.com](http://www.chemilac.com)