



STOVING ZINC CHROMATE PRIMER

Zinc Chromate Primer is an Stoving Primer. It is suitable as primer coat for Ferrous and Non-ferrous metal. It gives very good adhesion and anti-corrosive properties. It is suitable base coat for air-drying and stoving finishes where extra corrosion protection is required. It provides excellent intercoat adhesion to the topcoat.

Finish	Smooth & Matt
Colour	Grey Green/ Yellow
Viscosity	75 - 90 sec
Wt./ Ltr.	1.25 + or - 0.05 kg
Method of Application	Spraying/ Brushing
Stoving Schedule	120 C for ½ hr.
Spraying Viscosity	18 -22 sec
Thinner Recommended	Chemilac Stoving Thinner
Flexibility & Adhesion	Passed the test
Resistance to salt spray	Passed
Shelf life	one year

APPLICATION :

Remove all rust and greases from the surface by mechanical or chemical processes, make it dry, apply a coat of Chemilac Zinc chromate primer, provide 10 minutes flash off period. Store it at 120°C for 30 mins.

Notes :

All information given in this sheet are accurate to the best of our knowledge, no warranty given and no liability is accepted in respect of such information as conditions of applications are beyond our control.

CONTACT :

The Chemicals of India

(Prop. Chemilac Paints Pvt. Ltd.)

Plot No 36, Sector 27C, Faridabad-121003. Haryana

Phone : 91-129-2277382, 2277392

Fax : 91-129-2271607

Email : info@chemilac.com

visit us at : www.chemilac.com

